

# Known bugs and limitations in Prinergy Workflow 8.2

This section lists bugs and limitations that are known to exist in the software. If a future version of the software resolves a bug listed here, the bug is moved to the Fixed bugs section of the release notes accompanying that version of the software.

## Digital Job Ticket Editor

- In Windows, when using Digital Job Ticket Editor from within Workshop to edit a job ticket, it is intended to behave as a modal window, that is, it should prevent interactions with other elements of the Workshop client user interface until you have completed your interaction with Digital Job Ticket Editor. The current behavior on Windows is non-modal and incorrectly allows other elements in the Workshop client to be edited while Digital Job Ticket Editor is open. Therefore, it is not recommended to do anything in Workshop until you have finished using Digital Job Ticket Editor (clicking **Submit** or **Cancel**). [PRINERGY-40231]
- When using Digital Job Ticket Editor from within Workshop (**Send to Digital** command) or when opening Device Track from the Workshops **Tools** menu, the **Measurement Unit** defined in Workshop's Preferences is used and the **Weight Unit** and **Thickness Unit (Caliper)** are taken from Setup's Preferences.  
When Device Track is opened on the web (not from within Workshop), all unit settings in Digital Job Ticket Editor are taken from Setup's Preferences. [PRINERGY-42049]
- Settings available In RBA are not necessarily relevant to all digital devices. If you set a parameter which is not relevant for the selected device, this setting will be ignored when the rule is executed.
- Digital Job Ticket Editor can only display substrates in the **Substrate** drop down list that have sizes assigned. If a user creates a substrate on the digital device that lacks a defined size, it will not be sent to Prinergy and will not appear in Prinergy's Job Ticket Editor. [PRINERGY-46624]
- Digital Job Ticket Editor's **Substrate** drop down cannot display two substrates with the same name. If a user defines two substrates with the same name and size only one of them will be appear in Job Ticket Editor. [PRINERGY-46624]

## Device Track

- In order for Device Track to operate correctly within Internet Explorer 11, the setting **Display intranet sites in Compatibility View** must be disabled. This setting is enabled by default.  
To change the Compatibility View setting, in Internet Explorer, from the **Tools** menu, select **Compatibility View Settings**, and in the Compatibility View Settings dialog box, clear the **Display intranet sites in Compatibility View** check box, and click **Close** to apply the change. [PRINERGY-41259]
- In Internet Explorer 11, when you use the Refresh button in the browser to refresh Device Track, sometimes the data displayed is the data saved in its cache and not the data from the server.
- When using Internet Explorer with Device Track, Device Track requires version 11 or later. [PRINERGY-41757]
- Resizing columns in Device Track may result in columns being pushed off screen. [PRINERGY-41180]
- Digital output jobs may fail to output if moved from a Digital-Direct/Digital-Submit-connected device to a JDF-bi-directional-connected device. [PRINERGY-44863]
- An issue with status reporting coming from Kodak Xpo can cause the **In Process** queues in Prinergy's Device Track UI and Xpo to get out of sync and display output separation in the wrong order in Device Track. [PRINERGY-47843]
- After successful completion of output to EFI or Canon digital front-ends, the completed output jobs are absent from all queues in Device Track. [PRINERGY-47923] [PRINERGY-43780]
- In some older versions of EFI Fiery software, the number of inks reported was limited to five. This would cause jobs with more than five colors to incorrectly limit their color reporting back to Prinergy's Device Track UI to five colors. [PRINERGY-46698]
- When resubmitting a separation via Device Track, the separation receives a new Job ID from the device control software (Xpo or Print Console). This is due to the separation being treated as a new output instance rather than a remake of a previous output.

## TIFF Direct CTP connectivity

- When resubmitting a job to Print Console, two instances of the job will appear in the Print Console queue. The original job will include a note indicating it was removed by a Prinergy Workshop client, but still appears in the list. The second instance is the resubmitted job. [PRINERGY-46206]
- When adding a new media configuration, such as a new plate size, to a CTP output device, there is a delay of about one minute between adding it to the device and the new media appearing in Prinergy Workflow's UI via the new TIFF Direct connectivity. [PRINERGY-46439]
- When adding or removing punch settings on a CTP device, the status change is not communicated to Prinergy Workflow. If you add or remove a punch from a CTP device, you must disconnect the device from the Prinergy Administrator (UADM) and reconnect it to refresh the punch status. [PRINERGY-46404]
- The **Cut Media** check box in the **Device** section of the final output process template is not supported by Xpo and Print Console and should not be selected. [PRINERGY-46874]
- The **Media Registration** setting in the **Layout** section of the final output process template (**Layout > Media > Media Registration**) is not supported for Print Console. Use the **Punch Setting** instead (**Layout** section > **Placement > Punch Setting**). [PRINERGY-46856]
- The **Punch Setting** list contains all available punch settings for the selected device. When you select a punch setting, make sure you select a punch that is compatible with the selected media.
- VMR (Variable Mainscan Resolution) imaging is not supported with Xpo. [PRINERGY-47187]
- VMR (Variable Mainscan Resolution) imaging is not supported with Print Console. [PRINERGY-47338]
- When using a slugline mark with the updated sluglinemark positioning settings in the process template with direct (GDAPI) and TIFF Direct connectivity to CTP devices, the slugline mark may appear in the wrong location on the plate. [PRINERGY-46463]

## CTP connectivity

- When using a slugline mark with the updated sluglinemark positioning settings in the process template with direct (GDAPI) and TIFF Direct connectivity to CTP devices, the slugline mark may appear in the wrong location on the plate. [PRINERGY-46463]
- When adding or removing punch settings on a CTP device, the status change is not communicated to Prinergy Workflow. If you add or remove a punch from a CTP device, you must restart the JTP and define a new process template. [PRINERGY-46404]

## Setup

- Due to limitations in third-party JDF implementation, some settings may not flow back to Setup when updated in the front end software. This can include: binding edge, maximum density, layout, and sheet size options. [PRINERGY-39050] [PRINERGY-39982] [PRINERGY-40039] [PRINERGY-40045] [PRINERGY-41511] [PRINERGY-41632] [PRINERGY-41732] [PRINERGY-41745] [PRINERGY-41836] [PRINERGY-41906]
- Setup may have problems being installed via Microsoft Edge and Google Chrome. To install Setup via Microsoft Silverlight with Microsoft Edge, see the following support article from Microsoft: <https://support.microsoft.com/en-us/help/17472/windows-internet-explorer-11-fix-site-display-problems-compatibility-view#ie=ie-11>. [PRINERGY-41686]  
If you are having problems installing via Chrome, use a different browser. [PRINERGY-41032]
- Setup cannot be installed via Firefox on Mac OS X 10.12 because Firefox on Mac OS X 10.12 does not support Microsoft Silverlight. Use a different browser to install and to start Setup. [PRINERGY-44565]
- If you try to import substrates and/or reload device capabilities (in Setup > **Equipment > Digital Device**) from a connected press or DFE while this device is down, the substrates and/or device settings will no longer be visible in the Digital Job Ticket Editor when you submit a job. Once the device is up and running, you must re-import the substrates and/or reload the device capabilities so that they are visible again in the Digital Job Ticket Editor. [PRINERGY-45261]
- Setup is not localized with Chinese and Japanese on macOS Sierra (version 10.12) and macOS High Sierra (version 10.13) because of missing fonts. [PRINERGY-46365]  
To solve this issue, install the missing fonts:

1. MS Gothic.ttf -> for Japanese
2. .ttf -> for Chinese

## Job search

- In Job Finder, in the job advanced search feature, the search fails if you use the **is not** operator with a numerical value. [PRINERGY-38941]
- In Job Finder, in the job advanced search feature, if you select **Any**, the search results contain both jobs and pre-jobs that match the defined search criteria. [PRINERGY-39664]

## Integration with ColorFlow

The following limitations have been identified for using the ColorFlow software with Prinergy:

- Pages added to a ColorFlow-enabled job using Prinergy's Bypass Refine will have undefined Color Setup. This is expected behavior. Refining with ColorConvert enabled is recommended with ColorFlow integration.
- If you attempt to output a file with a different snapshot number from the number you defined in the refine process template, an error message appears.

## ColorConvert

The following ColorConvert problems have been identified:

- Color matching certain files with transparent objects can result in significant changes in appearance. The problem is file specific and is dependent on the transparency blending modes applied, the object's color and the DeviceLink or ICC profile used to colorconvert the objects. The problem occurs because each graphic and image object used in the transparency group is color-converted separately. Blending of the objects in the destination color space changes the appearance.  
**Recommendation:** Flatten the PDF files. If your PDF files contain RGB data, it is highly recommended to Color-Convert this data prior to flattening. Refer to Answer ID 72326 for best practices and setting up a 2-Step refine.  
**Note:** Contone proofing cannot be used to predict this issue when colormatching is performed on final output.
- ColorMatch vector overprint handling of certain files with transparency groups that also use overprint management can generate unexpected results. The new objects generated by the ColorMatcher vector overprint handling process end up ruining the appearance. Contone proofing with raster overprint handling cannot be used to predict the problem with vector overprint handling used on final output. See the Prinergy help for detailed descriptions about the processing differences between raster and vector overprint handling.  
**Recommendation:** Flatten the PDF files. If your PDF files contain RGB data, it is highly recommended to Color-Convert this data prior to flattening. Refer to Answer ID 72326 for best practices and setting up a 2-Step refine.
- RGB Transparency Blend Color Space is not supported. Blend spaces should only be defined as DeviceCMYK.  
**Recommendation:** Change the blend space in the input file or set up a Preflight+ profile to detect and /or fix the condition.
- ColorConvert is automatically selected in Vector Output process templates after you upgrade to Prinergy 8.2. This is due to a migration script bug. If you have a Basic License which doesn't enable ColorConvert, vector output will fail. If you are licensed for advanced Color Management, Color Conversion will be applied at output and may cause incorrect output. [PRINERGY-42167]  
**Workaround:** open any Vector Output process templates which should not have ColorConvert enabled and clear the **ColorConvert** checkbox.

## Preflight+

- callas process plans and profiles that create layers or contain unlicensed DeviceLinks are not supported.

- Kodak does not support or provide a license of callas pdfToolbox software. However, a copy of pdfToolbox (Preflight+ Profile Manager) is provided and licensed solely for the purpose of editing and creating preflight profiles that are to be used within Prinergy. Modification of the license as well as changing or upgrading the version of callas pdfToolbox that is provided with Prinergy is not recommended and not supported by Kodak. Kodak does not provide assistance or support for editing or creating new callas profiles. For information and support with the creation and editing of profiles, go to <http://www.callassoftware.com/en/support/documentation>.
  - **Note:** Kodak does support issues related to the integration of callas preflight within Prinergy Workshop.
  - Overview reports contain information from all pages in a multi-page PDF input file. When you open the report, it may contain information about pages you haven't selected.
  - Report Page links are supported only when you copy the full report.
  - callas fix-ups are "use at own risk". Exercise extra caution and check your proofs closely when applying fix-ups.
  - callas Profiles and Prinergy support different variations of the Chinese character set.
    - Simplified = ZH\_CN (callas) = PRC
    - Simplified = ZH\_Hans (Prinergy) = South East Asia and Singapore
  - Higher disk space demands—each PDF report contains a copy of the original Input PDF file.
  - To avoid Preflight+ becoming a bottleneck in the Refine process, it is advised to purchase the same amount of Preflight+ JTPs as Refine JTPs.
  - In translated reports, fix-up names in Preflight+ appear in English or in the language set in the operating system. If you chose to generate the Preflight+ reports in two or more languages (in Administrator: **Tools > Configure System > Preflight+ Settings > Report Language**, or in Setup: **Preferences > General > Preflight+ Settings > Report Language**), the names of the predefined profiles and fix-ups may appear in English or in the language set in the operating system in the translated reports instead of appearing in the defined language. [PRINERGY-38227]
  - The use of variables that prompt users for input are not supported.
  - New Librarys for organizing Checks and Fixups into categories.
- Note:** Profiles with Devicelink, Javascript and Variables are not supported.

## Flattener

Prinergy 8.2 introduces a new PDF Library 1507 responsible for flattening PDF files.

When flattening transparency the new flattener may create ICCBased images. If you set Preflight (Advanced or basic via **Normalize Input Control** or **Optimizer Digital Master Control**) to fail on ICCBased images, you may have to set these options to **Warn** or **Ignore**.

To avoid the more noticeable color shifts that could occur when viewing objects adjacent to flattener-created objects, it is advised to strip embedded profiles on Tagged Content via the Colormatcher section of the Refine Process Template. If performing a two-step Refine the profiles should be stripped via the 2nd Refine Process Template.

Tagging images as ICCBased could be beneficial to downstream processes but this may result in minor color shifts if you compare PDF files flattened in Prinergy version 8.2 against PDF files created in previous versions. Because of this it is recommended to reproof after upgrading to Prinergy 8.2.

Ink Coverage detection using Advanced Preflight may not be accurate on ICCBased images. Typically if you are flattening, you should be performing a two-step Refine. In a two-step Refine, detecting ink coverage is likely to occur on the 1st Refine prior to flattening, so you would not be subject to this limitation.

Please contact regional support and reference SKV 74201 to have a Flattener drop-in fix applied that will avoid the ICCBased tagging issues.

## Adobe PDF Print Engine

The Adobe PDF Print Engine (APPE) RIP cannot process PDF files containing embedded PostScript objects, including pages that were processed with PostScript bypass or with the OPI bypass features of Prinergy.

The APPE RIP is the preferred RIP for Prinergy.

APPE 4.7 adds support for a maximum of 123 spots colors. However, for Refine Thumbnail creation the maximum is 47. This is increased from a previous limit of 27 spot colors.

Observe the following precautions:

- Proofs and plates: In plating jobs with the APPE RIP, be careful with plates that were proofed with the previous APPE RIP. Because the RIPs are different, there is a slight chance of an interpretation difference between proof and plate. Ideally, jobs should be plated with the same version of Prinergy that was used to generate the proofs.  
**Note:** To avoid this situation you should coordinate hub and spoke configurations when upgrading Prinergy.
- Reprints: For reprints of jobs that were printed previously using an older RIP, it is recommended that you rerun proofs using the new RIP to ensure there are no unforeseen differences between the original press run and the reprint.

### **New PANTONE+ V3 libraries**

In keeping with PANTONE best practice guidelines, all previous PANTONE libraries have been removed as factory libraries and will no longer appear in your process templates. Previous Prinergy PANTONE libraries are provided in archive format and can be imported as user libraries, if desired, for legacy reprint jobs. For more details, see [About PANTONE libraries](#).

### **Maxtone CX, Maxtone FX, and Maxtone SX RIP**

Kodak Maxtone CX, Maxtone FX, and Maxtone SX screens are available for APPE RIP only. They are not available for use with CPSI RIP.

### **System spot color library L\*a\*b\* 2000**

When system spot color library L\*a\*b\* 2000 is added to a refine process template, it may not appear in the spot color libraries list but it will be available to be used by refine processes created from the refine process template. [PRINERGY-44022]

### **Refine to PDF/x-1a fails when Lab Spot Color Libraries are loaded and you are NOT converting Spots**

As of Prinergy 8.0, all factory Spot Color libraries were replaced with Pantone V3 Lab libraries. If you refine a file that contains a Spot Color that is defined in the Lab library, the Spot Colors Alternate Color Space will change to Lab. Since Lab is not allowed in PDF/x-1a, the process will fail.

To resolve this, you can remove the PANTONE V3 library or load a CMYK library, such as a legacy user or ColorBridge library (Answer ID 73041).

**Note:** If your incoming PDF has Spots with LAB Alternate Color space, you will want to have a CMYK Pantone library loaded, otherwise refine will also fail.

When converting Spots to Process, its recommended to use the new PANTONE V3 Library. See the About Pantone Libraries section of the Workflow Help for more information. (PRINERGY-43630)

### **Selecting “Replace variable marks in PDF content files” causes incorrect overprints on some objects**

When using this setting you must follow the procedure outlined in Partner Place Answer ID 69302. Failing to do so could result in serious Output problems.

## Register of a versioned page fails after the page has been opened in Acrobat on a Mac

If you open an LPV page in Acrobat and then re-generate it, the Register step will fail with an access violation message. This only happens when dealing with Windows 2008 servers and if the PDF has been opened on a Mac. [PRINERGY-29349]

**Workaround:** Unmount the Mac share.

## Additional Register JTPs configured to run on a secondary server are incorrectly homed on the primary server after restart

[Prinergy-34180]

## Mitered joins in text objects

Mitered joins in text objects with very large strokes may render incorrectly in low resolution output (300 dpi). [PRINERGY-38023]

## Windows Server 2008 R2 x64 and 2012 R2 operating systems

The following limitations have been identified when running Prinergy using the Windows Server 2008 R2 x64 or Windows Server 2012 R2 operating systems:

- Not all legacy Kodak computer-to-plate (CTP) devices have controlled release software that is compatible with Windows 2008 R2 or 2012 R2. Contact your Kodak representative to confirm if your CTP device has a compatible controlled release software available.
- Services for Apple Macintosh does not work with Windows Server 2008 R2 or 2012 R2. You must use SMB with named forks.
- After upgrading a Windows 2008 R2 server, SMB 2 will be incorrectly enabled which can cause performance and file consistency problems. Contact your local support representative to have it disabled again.
- Due to some cases of performance issues encountered in relation to SMB 3, Prinergy servers running Prinergy 8.2 versions are shipped with SMB 2 and 3 disabled by default. If you wish to enable SMB 3, all Prinergy servers and tertiary servers should be running Windows Server 2012 R2. If any of the Prinergy servers are running Windows Server 2008 R2 or any of the tertiary servers are not running Windows Server 2012 R2, SMB 2 and 3 need to be disabled so that SMB 1 is used. If this is not done, this can cause performance and file access/transfer issues. For assistance in disabling SMB 2 and 3, contact your local support representative.

## Security problem prevents starting Workshop on Mac OS X 10.8 and later

To enable activation of Workshop, perform the following steps: [PRINERGY-34821]

1. Open **System Preferences**.
2. Click **Security and Privacy**.
3. Click the **General** tab.
4. Click the lock icon located in the lower-left corner of the Security & Privacy window.
5. Enter your administrator credentials to enable making changes to the settings.
6. Under **Allow apps downloaded from**, select **Anywhere**.
7. Close **System Preferences**.

## Security problem prevents installing or starting Setup on Mac OS X 10.8 and later

To enable installation and/or activation of Setup, perform the following steps: [PRINERGY-41785]

1. In Safari, go to **Preferences > Security**.

2. In the Security window, click **Plug-in Settings...**
3. In the left pane, select the **Silverlight** check box.  
A list of servers is displayed in the right pane.
4. In the menu located next to the relevant server, select **Run in Safe Mode**.  
**Note:** In Mac OS X 10.12, press and hold down the Options (Alt) key, and in the menu located next to the relevant server, select **Run in Safe Mode**.
5. In the confirmation message that appears, click **Trust**.
6. Click **Done**.
7. Exit Safari for the changes to take effect.
8. Go to **System Preferences > Security and Privacy**.
9. On the **General** tab, click the lock icon located in the lower-left corner of the Security & Privacy window.
10. Enter your administrator credentials to enable making changes to the settings.
11. In the **Allow apps downloaded from** setting, make sure that the **App Store and identified developers** option is selected.
12. Close all windows.

### **Symantec Anti-virus may stop Prinergy from starting**

Some updates of Symantec Anti-Virus interpret Prinergy's ARAXI service as a threat. This has been addressed in newer updates to Symantec Anti-Virus. It is recommended that you update your virus definitions to avoid any problems with Symantec Anti-Virus affecting the operation of your Prinergy Workflow system. Alternatively, to exclude `araxi.exe` from the threat list, refer to [Partner Place answer ID: 72379](#). [PRINERGY-39813]

### **Network File System connectivity**

Prinergy does not support The Open Group UNIX NFS (Open Group UNIX Network File System). You can access UNIX servers using an SMB/CIFS protocol installed on the server (such as SAMBA).

### **Windows 2012 R2 servers localized to Japanese**

The fresh installer does not run on Windows 2012 R2 servers localized to Japanese. The server must be localized to English, or another supported non-Japanese localization before the fresh installer is run. Then, the server can be returned to Japanese localization. [PRINERGY-42036]

### **XMP Screening Tags**

The current implementation of XMP screening tags in Prinergy 8.2 applies the full set of XMP screening settings to the output. (PRINERGY-43209)

### **NexPress Job Ticket Editor cannot be launched by Digital Submit on Windows 10**

When running Digital Submit with NexPress on Windows 10, the Job Ticket Editor in Digital Submit fails to launch. [PRINERGY-41688]

**Workarounds:** To launch the NexPress Job Ticket Editor:

- Run Digital Submit and NexPress Job Ticket Editor on a workstation with a different operating system
- Manually launch the NexPress Job Ticket Editor outside Digital Submit.

### **HP Job Ticket Editor cannot be installed on Windows 8 and Windows 10**

The HP Job Ticket Editor is software available from HP which is used in Prinergy Workflow when connecting to HP digital presses. The latest version of the software available from HP is not compatible with Windows 8 and Windows 10 operating systems. HP is aware of the issue and will address it in a future product update. [PRINERGY-41575]

## HP

- When using a Hewlett Packard SmartStream DFE connected to multiple presses, each press connected to the SmartStream DFE consumes a connection license from Prinergy Workflow. If you have more presses connected to the SmartStream DFE than you have licenses for connections in Prinergy Workflow, Prinergy will not be able to connect with all presses connected to the SmartStream DFE. [PRINERGY-44364]
- If you try to import substrates and/or reload device capabilities (in Setup > **Equipment** > **Digital Device** ) from a connected press or DFE while this device is down, the substrates and/or device settings will no longer be visible in the Digital Job Ticket Editor when you submit a job. Once the device is up and running, you must re-import the substrates and/or reload the device capabilities so that they are visible again in the Digital Job Ticket Editor. [PRINERGY-44749]
- HP DFE with multiple connected presses does not recognize Prinergy server by its name. Make sure the Prinergy server name is correctly resolved on the DFE. For a DFE running on Windows, add the Prinergy host name and IP address in C:\Windows\System32\drivers\etc\host [PRINERGY-45428]

## Ricoh

- Perfect bound jobs with covers sent to Ricoh digital front end with PDF RIP Enhanced by Kodak type S4 may result in output with incorrect orientation. [PRINERGY-42077]
- Due to limitations in JDF implementation for Ricoh digital front end with PDF RIP Enhanced by Kodak type S4, layout options are not currently supported. [PRINERGY-39050]
- When sending a surface to Ricoh, the binding edge defined in the job will rotate 90 degrees clockwise due to geometry translation, but the end result of the output at the printer will be correct. If you have questions, contact your Kodak representative for assistance. [PRINERGY-42029]
- Jobs printed successfully move to On Hold queue rather than Completed queue in Device Track. This is a known Ricoh bug. [PRINERGY-45100]

## Konica Minolta

The status of coated or uncoated stock may not be imported or reflected correctly in Prinergy Setup for digital connections to Konica Minolta IC-602 or C1070 digital printer front end software. Job settings may need to be manually updated in the Konica Minolta software to complete output successfully. [PRINERGY-43211]

## EFI

- Due to a limitation in the bi-directional communication with EFI's software, completed jobs are do not appear in Prinergy Workflow's Device Track **Completed** queue and are not present in any queues upon completion. [PRINERGY-43780]
- Due to an EFI issue with bi-directional connectivity, Prinergy Device Track displays incorrect number of inks. [PRINERGY-46698]
- Due to a known EFI process with legacy JDF connectivity, jobs are not printed directly, but go to the **On Hold** queue first. [PRINERGY-46646]

## Prinergy Workshop localized to Japanese

Submitting a file to Prinergy Workshop localized to Japanese via drag and drop to a process template may cause Workshop to quit unexpectedly. [PRINERGY-43660]

## Legacy Workspace Features

Workspace is an alternative job and imposition interface that was introduced in Prinergy 6.0 and supported through Prinergy 7.5. There are several elements that remain in the Prinergy Workflow user interface that are not supported with Workshop client workflows, for example:

- The Generate Imposition action in Rules Based Automation

- Run List Assignment in the Automated Page Assignment (APA) feature
- Intent Events and Actions
- The RunList Event
- Scenario Actions
- Validation Actions
- The Assigned Scenario Success Event

**Note:** It is recommended that you avoid using unsupported actions.

### Prinermy Signature Select Limitations

Prinermy Signature Selection works in Preps 5 mode. Therefore, there are a number of limitations related to working with Preps 6 or later.

#### Editing impositions

- It is not possible to edit come-and-go, cut-and-stack, and multibinding style jobs with Signature Selection. If you try to edit an imposition that uses any of these styles, the **Use Prinermy Signature Selection** option will not be available in the Edit Imposition dialog box. Instead, you will be able to select **Use External Imposition Application** to start Preps.
- If you create a come-and-go or cut-and-stack imposition using Signature Selection, and then edit the imposition using Preps 6 or later, a warning message appears, indicating that the job was produced in an earlier version of Preps. You can ignore this message.

#### Importing Impositions

- Signature Selection does not support import of Preps 6 jobs with come-and-go or cut-and-stack binding styles. When creating a new imposition, if you select **Use existing Preps job** and select a Preps 6 job with a come-and-go or cut-and-stack binding style, an error message appears. You have the choice of selecting a different job file or using external imposition software to create the imposition.

#### Creating Impositions

- When you create a new imposition, the come-and-go or cut-and-stack binding styles are available in Preps 5 mode only.
- Preps 5 and 6 differ in the way that they display cut-and-stack and come-and-go jobs. In Preps 6, cut-and-stack jobs are shown as multiple webs, and come-and-go jobs are shown as multiple sections. In Prinermy Workshop, such jobs are displayed in the Preps 6 format, while in Signature Selection, they are displayed in the Preps 5 format. This is just a difference in display. The page assignment is correct and the imposition will print correctly.

### Auto Select in Prinermy Signature Selection

The use of Auto Select in Prinermy Signature Selection may produce different results from the use of Auto Select in Preps. Check that Auto Select produces the expected results.

If required, you can use **Move Up** or **Move Down** to adjust the signature order, or use **Add** or **Delete** to get the right signature.

To prevent the problem, edit the `PrepsPrinermy.cfg` and the `PrepsPrinermy.cfg.template` files to include the line:

```
AUTOSELECT_MINIMUM_PAGES:1.
```

### Dashboard

Regardless of the status of the enabled/disabled status of individual custom fields, all custom fields will be displayed in Dashboard. [PRINERGY-29639]

## **Limitations with SMB 2 and SMB 3 on Windows Servers in mixed environments**

Due to some cases of performance issues encountered in relation to SMB 3, Prinergy servers running Prinergy 8.2 versions are shipped with SMB 2 and 3 disabled by default. If you wish to enable SMB 3, all Prinergy servers and tertiary servers should be running Windows Server 2012 R2. If any of the Prinergy servers are running Windows Server 2008 R2 or any of the tertiary servers are not running Windows Server 2012 R2, SMB 2 and 3 need to be disabled so that SMB 1 is used. If this is not done, this can cause performance and file access/transfer issues. For assistance in disabling SMB 2 and 3, contact your local support representative.

## **RBA**

Rules Based Automation (RBA) may not start after upgrading to Prinergy Workflow 8.1.2. To address this issue, if encountered, see Partner Place answer [73601](#).

## **Licensing**

When rolling back from Prinergy Workflow 8.1.2 to a previously installed version, the Prinergy server may be unable to automatically retrieve a license for the previously installed version. In these cases, you will receive an alert from Prinergy Administrator that the current license is invalid. If you encounter this problem, please contact your service organization to address the issue. [PRINERGY-45926]

## **Windows 2016 Tertiaries**

Windows 2016 is not supported as a job home or as a tertiary for Prinergy Workflow. Additionally, if a Windows 2016 server is configured as a job home with a Prinergy Workflow system that includes an EPM+ failover server, when the EPM+ server is activated, it will not be able to access jobs from a job home on a Windows 2016 server. [PRINERGY-47070]

## **Creating Jobs Fails After Downgrading to 8.1.2 from 8.2.0**

If a downgrade to Prinergy 8.1.2 is required after upgrading to 8.2.0, errors may be encountered with creating jobs in the downgraded 8.1.2 server.

If you encounter this problem, contact your Kodak service representative to address the issue with your Prinergy system. [PRINERGY-46987]