

General Print options

Use the **General** tab in the Print dialog box to set up the basic output requirements.
Select **File > Print > General**.

Specify print range

Select this check box to print a partial job.

Use a dash to indicate a range, and use a comma to separate multiple values (1-4,9-12,21-24). Do not insert spaces.

Output Format, Divide by

For PS or PDF output, specify the components by which to divide a job's output. A separate file is generated for each component of that type.

- Optionally, use this setting in conjunction with a print range.
- Set up to 999 divisions for a job, with multiple output files generated per division.
- Without divided output, full jobs are printed by default, and if a problem is encountered, printing stops.
- With divided output, printing skips a problem file and goes to the next component file.
- Divided output files can be automatically placed into media-specific target folders that you define in the Media Configuration dialog box.
- Divided output is not available for JDF, PJTF, or PPF output.

The split file name format for divided output is defined on the **Output** tab in the Preferences dialog box.

Color Handling

None: Passes any color information through "as-is".

PDF Color mapping: Activates the **Color Separations** tab.

- If you print to PDF output, the RIP derives the color mapping information from the composite PDF output files.
- You can set up PS or Printer color-mapped output and print to PostScript devices that support in-RIP separations.
- Or, after setting up the mappings, switch the output type to PDF and generate color-mapped composite PDF output files.

Embed CIP3 cutting data

Adds the CIP3 cutting data to PJTF or JDF output files