

KODAK COLORFLOW Software

User Guide Document 731-02240A-AC

Welcome to the user documents for ColorFlow

To download a PDF format of this document, click the three dots on the top right corner and select **Export to PDF**. You can download a single page or a page with its child pages by selecting different templates.

Note: if JavaScript is disabled in your browser, the content or the functionality of this Website can be limited or unavailable.

ColorFlow is a color management application that is integrated with Prinergy to control color output. It is available in [Workflow edition](#) and [Pro Workflow edition](#). You can use the Workflow edition to create calibration curves for tonal or gray balance calibration, including G7. With the Pro Workflow edition, you can generate ICC Device and DeviceLink profiles for color matching.

ColorFlow is also available in [Measure edition](#) for chart creation and measurement in Kodak Managed Services (KMS) environments.

Tonal calibration for existing Harmony users:

- **Benefits of migrating to ColorFlow** – Simplifies curve creation and application, supports G7 for gray balance compensation and enables on-the-fly curve adjustments in Prinergy. See [ColorFlow Introduction for Harmony Users](#)
- **Migration guide** – Describes techniques for migrating curve management and use from Harmony to ColorFlow.

Tonal calibration for new Prinergy users:

- **Benefits of using ColorFlow** – Easy to apply international standards and ability to create gray balance curves
- **ColorFlow user interface** – Explains ColorFlow windows, icons, and processing states
- **Implement existing curves** – Curve creation based on a set of numbers
- **Plate curves** – Controls tonal response of the plate
- **Print curves** – Controls color response of the press
- **Reports** – Print characterization reports, Comparison reports, and Verification reports
- **Additional information** – [Training activity guide](#) and [video tutorials](#)

Color matching for Pro Workflow edition users:

- **Color setups** – Defines color relationships between the PCO, [SCO](#), and [color inputs](#), including [simulation](#) and [conversion](#) between color outputs
- **Device condition profile** – Used by Prinergy for color conversion operations
- **DeviceLink profile** – Used to align color on different output devices
- **Ink Optimizing Solution** – Reduces ink consumption and improves color stability