

Kodak JDF extensions for job creation

Use Kodak extensions at the prepress process group level to control the job-creation options that Prinergy applies. Kodak extensions for Business Link start with *sl/* and they are all optional.

Elements/Attributes for *sl:CreoSynapseJobCreate*

Element/Attribute	Format	Description and usage
@JobGroup	String	<ul style="list-style-type: none">• The name of the job group in which the new job should be created on the Prinergy server.• If the specified group does not already exist on the target system, it is created.• Multiple subgroups can be specified by using the pipe symbol.• The maximum length of each specified job group is 31 characters. Example: <code>JobGroup="New Jobs 2006 January"</code>
@JobVolume	URL	<ul style="list-style-type: none">• Path to the job-share on which the new job should be created.• This folder name must be a valid Prinergy share on a known secondary or tertiary server as configured through Prinergy Administrator.
@TemplateJobName	String	<ul style="list-style-type: none">• The exact name of an existing Prinergy job to be used as a template in creating the new job.• By default, all inheritable options of this template job are used when creating the new job.
@WebEnable	Boolean	<p>Indicates whether this job should be Web-enabled to permit customer access via InSite.</p> <p>A value of <code>True</code> is effective only if all of these points apply:</p> <ul style="list-style-type: none">• InSite is installed and connected to the target prepress system.• The specified CustomerID was previously mapped to an InSite customer account in the Prepress Customer Name column on the Administration Client Customer Mapping tab.

Elements/Attributes for \sl:CreoSynapseJobCreate and \sl:APAFile

Advanced Production Automation (APA) files are used to automate the assignment of pages to run-list positions in the Prinergy workflow. If a file URL is supplied in this field, Business Link copies that file into the appropriate subfolder of the Prinergy job.

Element /Attribute	Format	Description and usage
@ID		
@Status	Available	
@Class	Parameter	
@URL	URL	File location of the APA file. Example of a local path: file:\\c:\\lib\\apafile\\4pageCatalogAPAfile.apa Example of a remote path: file:\\YCS1234-567\\Fileshare\\4pageCatalogAPAfile.apa